

Elfin II

Two Printheads 1 inch High Resolution Inkjet Printer



Print Heights

With two stitched print heads, Print Heights can reach 1 inch (25.4mm)



Stand-alone print heads

Print heads and the controller can separately print two half inch



Connect to External Data Source

Through port of USB, Ethernet and RS232, printer can integrate with the external data



Built-in Photocell

Smart detection of external substrates with built-in photocell in print heads



7 inch LCD Touch Screen

7 inch bran-new color LCD touch screen



Aviation Connector

With Aviation connector to achieve high reliability and easy installation for bidirectional printing



Database Support

PC software supports the timely printing of data of MS Excel, MS Access, SQL2000, SQL2005, SQL2008 etc...



Smart Ink

Automatically recognize the ink types and identify the optimum printing parameters

Features

Selectable Languages

Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian;

Fonts

Default font is Arial, allows users to load the fonts they need;

Barcodes

UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, ENA 128, PDF417, DATAMATRIX, QR; (Allows user to add the barcode)

Date format

Two date types(production date, expiry date), different options of date format;

Support external database through PC software

MS Excel, MS Access, SQL;

Support data source from printer

Provide standard RS-232, Ethernet port and USB port, simplify the integration for customers;

*Date and counters can be switched to variable barcode printing



Technical Parameters

Technology

HP TIJ2.5;

Dimensions

controller(H*W*D): 210*135*37mm/8.3*5.3*1.46inch
one print head(H*W*D): 126*100*31mm/4.9*3.9*1.2inch
(Anti-shock cover is not included);

Power Supply

AC 90V-240V/50-60HZ, 90W (Dedicated AC);

Printable Heights (mm)

1~12.7mm (one print head)
1~25.4mm (two print heads)

Printing Speed

0~60m/min (300DPI)
0~30m/min (600DPI)

Resolution

50~600DPI

Printing Objects

Barcodes, Character, Numeric, Logo, date/time, Expiry Date, Shift code;

Port

- 1) Ethernet: 100Mb/S, synchronized control of multiple devices via PC;
- 2) USB2.0 Port: Support-Disk;
- 3) DB15: For external devices like photocell, synchronizer or alarm kit connection;

Interface

- 1) 7 inch 800 *480 color LCD touch screen;
- 2) With touch screen interface operation, easy to use;
- 3) Printer can work separately without PC software;

Ink management

- 1) Automatically recognize the ink types and identify the optimum printing parameters.
- 2) Guarantee of using genuine original HP ink.
- 3) Automatic measuring system for the usage of the ink

Mounting

Standard side and downside printing assembly, customers can fix it flexibly.

Product Certification

CE, FCC;

Environment

- 1) Working Environment: -10°-- +55°C; 10%-85%RH;
- 2) Storage Environment: -25°-- +80°C; 10%-90%RH;

Ink Solutions

- 1) Support 42ml, 370ml and 350ml cartridges of HP TIJ2.5 technology;
- 2) Support various colors of ink: black, red, green, blue;
- 3) Support Porous, semi-porous and non-porous materials.